


STYLE REF: **RF290**
STYLE NAME: **SILT**

Rock Fall®
INDUSTRY DEFINING SAFETY FOOTWEAR

SPECIFICATION: EN ISO 20345:2022+A1:2024 S5S CI HRO SC AN FO SR | UK 3 - 14 (INC 6.5 AND 10.5) | COLOUR NAVY
100% NON-METALLIC, WITH PROTECTIVE TOECAP AND MIDSOLE, SILT IS HIGHLY ROBUST AND DEVELOPED WITH SPECIALIST DURABILITY MATERIALS INCLUDING FORCE10® COMPONENTS, AN ACTIV-STEP® PU FOOTBED AND 5MM NEOPRENE UPPER.

RF290



FORCE10 **activ**
step

Upper Material

Waterproof 5mm neoprene upper with high vis band

Protective Components

Protective fibreglass toecap and composite anti-penetration flexi-midsole

Lining Materials

Moisture wicking breathable mesh fabric lining

Scuff Cap and Outsole

FORCE10® solid nitrile rubber outsole and rubber scuff cap - With extraordinary abrasion and heat resistance and a cold performance level tested to -40 °

Footbed

Activ-Step® PU anti-fatigue comfort footbed

SUBJECT TO CHANGE WITHOUT PRIOR NOTICE: 01/05/2021

Find this product at <https://www.rockfall.com/products/silt>

Browse all products at <https://www.rockfall.com/products>

PROUDLY MANUFACTURED BY ROCK FALL UK, MAJOR HOUSE, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS



Issued to:

Rock Fall UK Ltd
Major House
Unit 1/3 Wimsey Way
Alfreton
Derbyshire
DE55 4LS
United Kingdom

Notified Body: 2777

SATRA customer number: P1769

EU Type-Examination Certificate

Certificate number: 2777/10367-04/E00-00

This EU Type-Examination Certificate covers the following product group(s) supported by testing to the relevant standards/technical specifications and examination of the technical file documentation. It has been issued Under Module B of Regulation 2016/425 on personal protective equipment. This product group has been shown to satisfy the applicable essential health and safety requirements as a Category II product.

Product reference:

Rock Fall RF290 SILT Navy/Orange
Rock Fall RF280 Meadow Green

Description:

Safety Footwear comprising:

Height of upper: Knee boot
Upper: Rubber
Lining: Mesh
Collar: Neoprene/ Spandex
Toecap: Fiberglass SY-LB-L2
Perforation resistance insert: Composite SY-BA-L2
Construction: Cemented
Sole: Rubber
Sole Pattern: SY-XX-L2

Available colour: Navy/Orange; Green

Size Range: 3 - 14

Classification:

EN ISO 20345:2022+A1:2024 S5S CI HRO SC AN FO SR

Standards/Technical specifications applied:
EN ISO 20345:2022+A1:2024

Technical reports/Approval documents:
Intertek: LEHTX00100988, LEHTX00101244, LEHTX00100770, LEHTX00100469, LEHTX00100659A1, LEHTX101658, GZHT90732584, GZHT90752378, GZHT90773512, GZHT90778384, GZHT90756231, GZHT90661552, GZHT90891889(S1), GZHT91155522, GZHT91171812, GZHT91206561, GZHT91219299, GZHT91231772, GZHT91258792.
SGS: SL92229342061101FW
SATRA: FWT0269615/1815, SPC0333077 2225 1

Signed on behalf of SATRA:

Geoff Graham

Date first issued: 26/04/2018
Date of issue: 24/09/2024
Expiry date: 24/09/2029

EU DECLARATION OF CONFORMITY

Rock Fall UK, Major House,
Unit 1/3, Wimsey Way,
Alfreton, Derbyshire, DE55 4LS
United Kingdom
Tel: **01773 608616**
Email: **sales@rockfall.com**
rockfall.com

The manufacturer or his nominated representative established in the community;

ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM

Declares that the PPE described hereafter;

ROCK FALL RF290 Silt

Is in conformity with the provisions of PPE Regulation EU 2016/425 for **Category II** and, where such is the case, with the national standard transposing the union harmonised standard no. **EN ISO 20345:2022+A1:2024**

This declaration of conformity is issued under the sole responsibility of the manufacturer;

ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM

Is identical to the PPE submitted to: **SATRA Technology Europe Limited, Bracetown**

Business Park, Clonee D15Y N2P. Notified Body 2777. who performed the Eu type

examination (Module B) and issued the EU type -examination certificate: **2777/10367-04/E00-00**

The PPE is subject to the procedure set out in **Module C** of the PPE Regulation EU 2016/425 under the supervision of the notified body: **SATRA Technology Europe Limited, Bracetown Business Park, Clonee D15Y N2P. Notified Body 2777.**

Signature:

A handwritten signature in black ink, appearing to read "R. K. N. O. O. N.", written over a large, light grey, stylized mountain peak graphic.

Position: Director

Date: 24/09/2024



Issued to:

Rock Fall UK Ltd
Major House
Unit 1/3 Wimsey Way
Alfreton
Derbyshire
DE55 4LS
UK

Approved Body: 0321

SATRA customer number: P1769

UKCA Type-Examination Certificate

Certificate number: AB0321/16478-01/E00-00

This UKCA Type-Examination Certificate covers the following product group(s) supported by testing to the relevant standards/technical specifications and examination of the technical file documentation:

Following the UKCA Type-Examination this product group has been shown to satisfy the applicable essential health and safety requirements of the PPE Regulation (2016/425) as brought into UK law and amended as a Category II product.

Product reference:

Rock Fall RF290 SILT

Description:

Blue vulcanised rubber wellington boot with a neoprene upper, fibreglass toe cap, composite penetration resistant midsole and a cemented rubber outsole.

Rock Fall RF280 Meadow

Same as above but Green in colour

Classification:

EN ISO 20345:2011 S5 CI HRO SRC

Size Range: 36 – 48 EUR

Standards/Technical specifications applied:

EN ISO 20345: 2011

Technical reports/Approval documents:

Intertek: LEHTX00100988, LEHTX00101244, LEHTX00100770, LEHTX00100469, LEHTX00100659A1, LEHTX101658, GZHT90732584, GZHT90752378, GZHT90773512, GZHT90778384, GZHT90756231, GZHT90661552, GZHT90891889(S1).
SATRA: FWT0269615/1815.

Signed on behalf of SATRA:

Pete Doughty

Date first issued: 29/04/2021

Date of issue: 29/04/2021

Expiry date: 29/04/2026

UKCA DECLARATION OF CONFORMITY

The manufacturer or his nominated representative established in the community;

ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM Declares that the

PPE described hereafter;

ROCK FALL RF290 Silt

Is in conformity with the provisions of PPE Regulation EU 2016/425, as brought into UK Law and amended, for **Category II** and, where such is the case, with the national standard transposing the union harmonised standard no. **EN ISO 20345:2011**

This declaration of conformity is issued under the sole responsibility of the manufacturer;

ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM

Is identical to the PPE submitted to: **SATRA Technology Centre Limited, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD United Kingdom. Approved Body 0321.** who performed the UKCA type examination (Module B) and issued the UKCA type -examination certificate: **AB0321/16478-01/E00-00**

The PPE is subject to the procedure set out in **Module C** of the PPE Regulation EU 2016/425, as brought into UK Law and amended, under the supervision of the notified body: **SATRA Technology Centre Limited, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD United Kingdom. Approved Body 0321**

Signature:

A handwritten signature in black ink, appearing to read "R. Kinson".

Position: Director

Date: 29/04/2021



2 Cold Insulation Of Outsole Complex (Whole Footwear) (EN ISO 20344:2021, 5.16, Modified)

Test Condition:	
Thermal Transfer Medium:	Stainless Steel Balls With 5 mm Diameter And A Total Mass Of (4±0.1) kg
Temperature Of Cold Box:	-40 °C
Test Period:	(30±1) Minutes

Sample	Size	Results	Applicant's Requirement	Pass/Fail														
-	49	<p>Left</p> <p>Except For The Insock, The Insulation Is Incorporated In The Footwear That It Cannot Be Removed Without Damaging The Footwear.</p> <p>The Sample Exhibited Less Than a 10°C Change Within 30 Minutes The Result Are Below: Internal Temperature Of The Freezer -40°C Initial Temperature Of The Upper Surface Of The Insole 23.5°C Time In Cold Enviroment</p> <table border="0"> <tr> <td>5 Min.</td> <td>23.2°C</td> </tr> <tr> <td>10 Min.</td> <td>23.1°C</td> </tr> <tr> <td>15 Min.</td> <td>22.8°C</td> </tr> <tr> <td>20 Min.</td> <td>21.6°C</td> </tr> <tr> <td>25 Min.</td> <td>20.0°C</td> </tr> <tr> <td>30 Min.</td> <td>18.6°C</td> </tr> <tr> <td>Total Temperature Change</td> <td>5.0°C</td> </tr> </table>	5 Min.	23.2°C	10 Min.	23.1°C	15 Min.	22.8°C	20 Min.	21.6°C	25 Min.	20.0°C	30 Min.	18.6°C	Total Temperature Change	5.0°C	*	Pass
5 Min.	23.2°C																	
10 Min.	23.1°C																	
15 Min.	22.8°C																	
20 Min.	21.6°C																	
25 Min.	20.0°C																	
30 Min.	18.6°C																	
Total Temperature Change	5.0°C																	

Remark: * = Max. 10°C Temperature Decrease On The Upper Surface Of The Insole Or Insock.
 Except For The Insock, The Insulation Shall Be Incorporated In The Footwear In Such A Manner That It Cannot Be Removed Without Damaging The Footwear.

Expanded Uncertainty: 0.36°C, With k= 2.01 At 95% Confidence Level.





End Of Report

This report is made solely on the basis of your instructions and/or information and materials supplied by you. It is not intended to be a recommendation for any particular course of action. Intertek does not accept a duty of care or any other responsibility to any person other than the Client in respect of this report and only accepts liability to the Client insofar as is expressly contained in the terms and conditions governing Intertek's provision of services to you. Intertek makes no warranties or representations either express or implied with respect to this report save as provided for in those terms and conditions. We have aimed to conduct the Review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or wilful misconduct. No copy of the test report(except for full text copy) shall be made without the written approval by Intertek.

Remark:

1. As Requested by the Applicant, For Details Refer to Attached Page (S).
2. All the tested item are tested under the standard condition.
3. The report is valid with commission test only for the test samples in the case of delivering samples by clients.