

FEATURES



Anti-Static



SRC Slip Resistance



Stainless Steel
Midsole



Steel Toecap



Larger Sizes

INDUSTRIES



Automotive
and Aerospace



Emergency Services



Security



Facility Management

Product Details

Colour: Black
Size Range: UK 6-16
Height: 5 inches



PRODUCT DESCRIPTION

Anti-Static, Fuel Oil Resistant Outsole,
Fully Sustainable Packaging, Large
Sizes 14+, SRC Slip Resistance,
Stainless Steel Midsole, Steel Toecap

TECHNOLOGIES & ACCREDITATIONS

MATERIAL BREAKDOWN

Upper Material

Coated Leather, LWG Certified

Lining

100% Polyester Mesh

Webbing and Trims

100% Polyester

Footbed

EVA Foam + 100% Polyester Top Mesh

Protective Toe Cap

Steel

Protective Midsole

Stainless Steel

Outsoles

Dual Density PU

Category	SB	S1	S2	S3/L/S	S4	S5/L/S	S6	S7/L/S
Class 1	✓	✓	✓	✓	×	×	✓	✓
Class 2	×	×	×	×	✓	✓	×	×
200 Joules Toecap	✓	✓	✓	✓	✓	✓	✓	✓
Closed heel Area	×	✓	✓	✓	✓	✓	✓	✓
Energy Absorption Of Seat Region	×	✓	✓	✓	✓	✓	✓	✓
Anti-Static	×	✓	✓	✓	✓	✓	✓	✓
Water Penetration And Absorption	×	×	✓	✓	×	×	✓	✓
Perforation Resistance According To The Type	×	×	×	✓	×	✓	×	✓
Cleated Outsole	×	×	×	✓	×	✓	×	✓
Water Resistance Of The Entire Shoe	×	×	×	×	×	×	✓	✓

EN 2022 SPECIFICATION

Safety footwear is classified in the UK and EU by the EN 20345 standard using a categorisation of S1 through to S7 to quickly determine the level of incorporated safety components. This is further supported by letter codes for additional safety components or tests the footwear has undergone.

For further information contact the Rock Fall sales team.

Always check with your health and safety management if you are unsure of the appropriate specification required by your workplace.

Class 1 refers to footwear made from leather & other materials, excluding all polymeric and all rubber footwear

Class 2 Refers to all polymeric footwear including all rubber footwear.

S3, S5, S7 Specify metallic midsole tested at 1100N.

S3L, S5L, S7L specify non-metal midsole tested at 1100N with a 4.5mm nail.

S3S, S5S, S7S specify non-metal midsole tested at 1100N with a 3mm nail.

Please note that the EN20345:2022 specification **does not** necessarily apply to the footwear represented here, and that there are further specifications attaining to specific safety tests and standards. Always check specification and standards of the footwear before purchase. For more information on specifications and standards, get in touch with our team for complete guide.

WELLBEING & COMFORT

When you spend your working day on your feet, discomfort and incorrect footwear can cause serious long-term issues. That's why our footwear is designed to support your feet where they need it most, and we have a wide variety of styles to fit every kind of foot. Make sure your footbed is providing the correct arch support, and that your footwear is the correct size for you feet.

FOOTWEAR CARE

Keeping your safety footwear in a good condition helps keep them comfortable and extend their useful life. Always make sure to keep the upper and sole clear of extensive mud or residue, using a brush and warm water to clean. Never dry out footwear using heat (such as placing them near a radiator) always allow them to dry naturally. Use a leather nourishment or dubbin wax to keep leather materials from drying out.



Issued to:

Rock Fall UK Ltd
Major House
Unit 1/3 Wimsey Way
Alfreton
Derbyshire
DE55 4LS
UK

Notified Body: 2777

SATRA customer number: P1769

EU Type-Examination Certificate

Certificate number: 2777/20379-01/E00-00

This EU Type-Examination Certificate covers the following product group(s) supported by testing to the relevant standards/technical specifications and examination of the technical file documentation:

Following the EU Type-Examination this product group has been shown to satisfy the applicable essential health and safety requirements of Annex II of the PPE Regulation (EU) 2016/425 as a Category II product.

Product reference:

ProMan TC310 Oregon
Chelsea Safety Boot

Description:

Ankle safety boot comprising black smooth action leather uppers with synthetic linings. Black elasticated lateral bands serve as the fastening system, with steel toecap referenced 1701G, steel perforation resistant insert referenced MRA01 and an injection moulded PU outsole.

Classification:

EN ISO 20345:2011 S1P SRC

Size Range: 3 – 16 UK

Standards/Technical specifications applied:
EN ISO 20345: 2011

Technical reports/Approval documents:

INTERTEK: GZHT91008215, GZHT91008155, GZHT90990459, GZHT90710695, GZHT90855083(S1), GZHT90808030, GZHT90822597, GZHT90985248, GZHT90994010, GZHT90892397

Signed on behalf of SATRA:

Quincey Brown

Date first issued: 22/02/2022

Date of issue: 22/02/2022

Expiry date: 22/02/2027

EU DECLARATION OF CONFORMITY

Rock Fall UK, Major House,
Unit 1/3, Wimsey Way,
Alfreton, Derbyshire, DE55 4LS
United Kingdom
Tel: **01773 608616**
Email: **sales@rockfall.com**
rockfall.com

The manufacturer or his nominated representative established in the community;

ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM

Declares that the PPE described hereafter;

ProMan TC310 Oregon

Is in conformity with the provisions of PPE Regulation EU 2016/425 for **Category II** and, where such is the case, with the national standard transposing the union harmonised standard no. **EN ISO 20345:2011**

This declaration of conformity is issued under the sole responsibility of the manufacturer;

ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM

Is identical to the PPE submitted to: **SATRA Technology Europe Ltd, Bracetown Business Park, Clonee, D15YN2P. Republic of Ireland. Notified Body 2777.** who performed the Eu type examination (Module B) and issued the EU type -examination certificate: **2777/20379-01/E00-00**

The PPE is subject to the procedure set out in **Module C** of the PPE Regulation EU 2016/425 under the supervision of the notified body:

SATRA Technology Europe Ltd, Bracetown Business Park, Clonee, D15YN2P. Republic of Ireland. Notified Body 2777.

Signature:

A handwritten signature in black ink, appearing to read "R. K. Wilson", written over a large, light gray, stylized mountain peak graphic that serves as a background for the signature area.

Position: Director

Date: 22/02/2022